

## Approvals:



## Combi storage heaters

### Key features

- Combines economic tariff rate storage heater with a fast and responsive Warmflow fan heater for instant room heating.
- The slimmest storage combination heater available.
- Sensamatic fully automatic storage heater output ensures room comfort levels are maintained throughout the day without user intervention.
- The Warmflow fan heater has manually adjustable room temperature sensing thermostatic control accurate to within 0.5°C.
- Quiet, low velocity Warmflow fan.
- All controls are concealed behind a lockable flap.
- Hydraulic input charge control thermostat provides auto-set input charge control.
- Fan heater ratings can be set on full or half load (installation option).
- Automatic fan heater switch-off during off-peak tariff periods (installation override option).

### The range

The Supaslim Combi heater is designed to combine economic and low-cost storage heating with an independently thermostat-controlled fan heater. Effectively two heaters in one, the built-in fan can provide heat on its own or in combination with the storage heater for a rapid boost to room temperature.

### Technical specification

- Elements (storage) – mineral insulated stainless steel sheathed.
- Insulation – opacified siliceous aerogel and mineral fibre mat.
- Storage core – high density iron oxide compound.
- Fan unit – crossflow.
- Controls – hydraulic head temperature compensated, room and storage core temperature sensitive, auto-set charge control.
- Protection – two level thermal safety overheat.
- Supply – 230/240V AC single phase.

### Product variations

	<b>TSR12ACW</b>	<b>TSR18ACW</b>	<b>TSR24ACW</b>
Rating Storage	1.7kW	2.5kW	3.4kW
Direct Acting	1/0.5kW	1.5/0.75kW	2.0/1.0kW
Charge Acceptance (7hrs)	11.8kWh	17.6kWh	23.5kWh
Weight (kg)	78kg	114kg	149kg
No. of Elements	2	3	4
No. of Core Bricks	8	12	16
Height A	760mm	760mm	760mm
Width B	560mm	788mm	1016mm
Depth C	170mm	170mm	170mm

